

# PLANTASTAR 400 W E40

PLANTASTAR-T | High-pressure sodium vapor lamps for open and enclosed luminaires



## Areas of application

- Greenhouses
- Suitable for growth of fruit due to emission of photosynthesis optimised light
- Application only in suitable luminaires

#### **Product benefits**

- Shorter production times
- Control over blossoming

#### Product features

- Average lifetime: 12,000 h
- Provides light for the photosynthesis in plants
- Photon flux: > 90 % after 12,000 h
- High-pressure sodium lamp especially for greenhouse lighting



# Product datasheet

#### Technical data

### **Electrical data**


Nominal wattage	400.00 W
Rated wattage	400.00 W
Lamp current	4.52 A
Nominal voltage	100 V
Ignition voltage	4.0 / 5.0 kVp <sup>1)</sup>

<sup>1)</sup> Minimum / Maximum

### Photometrical data

Photon flux	725 μmol/s
Photon flux efficacy	1.7 μmol/s/W
Color rendering index Ra	25
Color temperature	2000 K
Rated LLMF at 2,000 h	0.98
Rated LLMF at 4,000 h	0.97
Rated LLMF at 6,000 h	0.96
Rated LLMF at 8,000 h	0.95
Rated LLMF at 12,000 h	0.94
Rated LLMF at 16,000 h	0.94

# Dimensions & weight





Diameter	47.0 mm
Length	285.0 mm
Light center length (LCL)	175.0 mm
Product weight	174.00 g

## Temperatures & operating conditions

# Product datasheet

Maximum permitted outer bulb temperature	400 °C
Maximum permitted base edge temperature	250 °C

## Lifespan

Rated lamp survival factor at 2,000 h	0.99	
Rated lamp survival factor at 4,000 h	0.99	
Rated lamp survival factor at 6,000 h	0.98	
Rated lamp survival factor at 8,000 h	0.98	
Rated lamp survival factor at 12,000 h	0.97	
Lifespan B50	32000 h	
Lifespan B10	24000 h	
Lifespan B5	20000 h	

# Additional product data

Base (standard designation)	E40	
Design / version	Clear	
Mercury content	21.0 mg <sup>1)</sup>	

<sup>1)</sup> Maximum

## **Capabilities**

Dimmable	No
Burning position	Any
Enclosed luminaire required	No

## **Certificates & standards**


Energy efficiency class	A++	
Energy consumption	440 kWh/1000h	

# **Country specific categorizations**

ILCOS	ST-400-H/E-E40-47/285

### Product datasheet

### **Light Distribution**



Spectral power distribution

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300620084	PLANTASTAR 400 W E40	Shipping carton box 12	268 mm x 345 mm x 221 mm	20.43 dm³	2694.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.